



AL-JI-AN/A2N/A3N/A4N

**20w / 40w / 60w
MODELS**

**80w / 100w
MODELS**

**150w / 180w
200w / 300w MODELS**


Certifications



A Width	B Height	C Depth	Wattages
10.4"	6.3"	8.1"	20w / 40w / 60w
12.6"	9.4"	6.5"	80w / 100w
15"	9.1	10.6	150w / 180w / 200w / 300w

DESCRIPTION

This luminaire can be used as a spot light, down light, tunnel light, high bay light, flood light and wall pack for general illumination in hazardous locations.

Specifications

Model Name	AL-JI-A2N-CID1-20	AL-JI-A2N-CID1-40	AL-JI-A2N-CID1-60	AL-JI-AN-CID1-80	AL-JI-AN-CID1-100	AL-JI-A3N-CID1-150	AL-JI-A3N-CID1-180	AL-JI-A3N-CID1-200	AL-JI-A4N-CID1-150	AL-JI-A4N-CID1-180	AL-JI-A4N-CID1-200	AL-JI-A4N-CID1-300	AL-JI-A4N-CID1-400
Input Wattage (W)	20W	40W	60 W	80W	100W	150W	180W	200W	150W	180W	200W	300W	400W
Voltage (V)	U (120-277V) / HV (227-480V) / DC (12-48V)												
Lumen Output (lm)	2,600 lm	5,200 lm	7,800 lm	10,400 lm	10,400 lm	21,000 lm	25,200 lm	28,000 lm	21,000 lm	25,000 lm	28,000 lm	42,000 lm	56,000 lm
Efficacy (lm/W)	130 lm/W					140 lm/W							
Color Rend. Index	80+ CRI												
Color Temperature	22 (2,200k) - 40 (4,000k) - 50 (5,000k) - 70 (7,000k)												
Longevity (L70)	50,000 Hours												
Amb. Temperature	-40°C to 60°C / -40°F to 140°F												
Warranty	5 years												

Ordering Guide

EG: AL-JI-A3N-CID1-150-8-50-HV

Model Name	Wattage	CRI	CCT	Driver
AL-JI-A2N	20: 20 W	8: >80	22: 2200k	U: Universal 120-277V HV: 277-840V DC: 12-48V
	40: 40 W		40: 4000k	
	60: 60 W		50: 5000k	
AL-JI-AN	80: 80 W		70: 7000k	
	100: 100 W			
AL-JI-A3N	150: 150 W			
	180: 180 W			
	200: 200 W			
AL-JI-A4N	150: 150 W			
	180: 180 W			
	200: 200 W			
	300: 300 W			
	400: 400 W			