


AL-JI-BN/B2N/B3N/B4N

B2N
BN
B3N
B4N


Dimensions



	A Diameter	B Height	C Height	Wattages
B2N	9.2"	9"	14"	20w / 40w
BN	10.6"	6.5"	15.5	60w / 80w
B3N	14.62"	6.5"	15.5	100w / 120w / 150w / 200w



Dome Reflective Hood



Angled Reflective Hood

DESCRIPTION

This luminaire can be used as a spot light, down light, tunnel light, flood light and wall pack for general illumination in hazardous locations.

Specifications

Model Name	AL-JI-B2N-C1D1-20	AL-JI-B2N-C1D1-40	AL-JI-BN-C1D1-60	AL-JI-BN-C1D1-80	AL-JI-B3N-C1D1-100	AL-JI-B3N-C1D1-120	AL-JI-B3N-C1D1-150	AL-JI-B3N-C1D1-200	AL-JI-B4N-C1D1-250	AL-JI-B4N-C1D1-300	AL-JI-B4N-C1D1-350	AL-JI-B4N-C1D1-400
Input Wattage (W)	20W	40W	60 W	80W	100W	120W	150W	200W	250W	300W	350W	400W
Voltage (V)	U (120-277V) / HV (227-480V) / DC (12-48V)											
Lumen Output (lm)	2,600 lm	5,200 lm	7,800 lm	10,400 lm	10,400 lm	21,000 lm	25,200 lm	28,000 lm	21,000 lm	25,000 lm	28,000 lm	42,000 lm
Efficacy (lm/W)	130 lm/W				140 lm/W							
Color Rend. Index	80+ CRI											
Color Temperature	22 (2,200k) - 40 (4,000k) - 50 (5,000k) - 70 (7,000k)											
Longevity (L70)	50,000 Hours											
Amb. Temperature	-40°C to 60°C / -40°F to 140°F											
Warranty	5 years											

Ordering Guide

EG: AL-JI-B3N-C1D1-150-8-50-HV

Model Name	Wattage	CRI	CCT	Driver
AL-JI-B2N	20: 20 W 40: 40 W	8: >80	22: 2200k 40: 4000k 50: 5000k 70: 7000k	U: Universal 120-277V HV: 277-840V DC: 12-48V
AL-JI-BN	60: 60 W 80: 80 W			
AL-JI-B3N	100: 100 W 120: 120 W 150: 150 W 200: 200 W			
AL-JI-B4N	250: 250 W 300: 300 W 350: 350 W 400: 400 W			