




Dimensional Drawing



Specifications

Model Name	AL-JI-GN-CID1-10	AL-JI-GN-CID1-20	AL-JI-GN-CID1-30	AL-JI-GN-CID1-40	AL-JI-GN-CID1-50
Input Wattage (W)	10 W	20 W	30 W	40 W	50 W
Voltage (V)	U (120-277V)				
Lumen Output (lm)	1,400 lm	2,800 lm	4,200 lm	5,600 lm	7,000 lm
Efficacy (lm/W)	140 lm/W	140 lm/W	140 lm/W	140 lm/W	140 lm/W
Color Rendering Index	>80 CRI				
Color Temperature	22 (2,200k) - 40 (4,000k) - 50 (5,000k) - 70 (7,000k)				
Dimming Compatible	NO				
Longevity (L70)	50,000 Hours				
Ambient Temperature	-40°C to 65°C / -40°F to 149°F				
Warranty	5 years				

This luminaire can be used as a spot light, down light, tunnel light, flood light, and wall pack for general illumination in hazardous locations.

FEATURES

- High quality SMT LED and Meanwell Driver.
- Light-weight design by aircraft aluminum.
- Heavy-duty and high impact resistance.
- Three connection cable entry points.
- Replaceable LED board and drivers.
- Integrated junction box for driver with emergency back up.
- Dimmable and battery back up function available.
- Marine rating powder coated appearance treatment.

Ordering Guide

EG: AL-JI-GN-CID1-~~30~~-8-40-U

Model Name	Wattage	CRI	CCT	Driver
AL-JI-GN-CID1	10: 10 W 20: 20 W 30: 30 W 40: 40 W 50: 50 W	8: >80	22: 2200k 40: 4000k 50: 5000k 70: 7000k	U: Universal 120-277V